

**Declaration of Performance
No. 202-DOP-001 – v1.0**

1. Unique identification code of the product-type:

**202 – GV Standard PitchVent – Double Glazed (6-16-6 Toughened)
Opening roof-window**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under article 11(4) of the CPR:

**202 – GV Standard PitchVent – Double Glazed (6-16-6 Toughened)
Opening roof-window**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

An in-plane opening roof-window for the admission of natural light and ventilation into a domestic or commercial location, with both the unit and the roof inclined at an angle of between 15° and 60° and placed at least 800mm above floor level.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Glazing Vision Ltd
Saw Mills Road
Diss
Norfolk IP22 4RG
UK**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

As point 4

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 14351-1:2006+A2:2016



FMS96998

EMS613885

Glazing Vision Ltd, Saw Mills Road, Diss, Norfolk, IP22 4RG

Registered in England. No. 2987024 VAT No. 637 7241 26

01379 658300 info@glazingvision.co.uk

8. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Resistance to wind load	Test pressure	Class 4
	Frame deflection	Class C
Resistance to snow load		6-16-6
		Outer: Toughened Inner: Toughened
Reaction to fire		Class A1
External fire performance		NPD
Watertightness	Non-shielded (A)	Class 9A
	Shielded (B)	NPD
Impact resistance		NPD
Load-bearing capacity of safety device		N/A
Acoustic performance		NPD
Thermal transmittance		1.5 W/(m ² .K)
Radiation properties	Solar factor	0.51
	Light transmittance	0.71
Air permeability		Class 4

EN 14351-1:2006
+A2:2016

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of Glazing Vision Ltd by:

Jeremy Dunn



Technical Director

.....
20/02/2018
.....
(place and date of issue)



FM596998 EMS613885